

ZOOM



XB LT

LIGHT INTERMEDIATE
EN / LTF B

TECHNICAL DATA

Size	75	85	95	105	115	125
Cells	49	49	49	49	49	49
Area projected (m ²)	18,07	19,29	20,78	22,31	23,9	25,54
Span projected (m)	8,35	8,63	8,95	9,28	9,6	9,93
AR projected	3,86	3,86	3,86	3,86	3,86	3,86
Area flat (m ²)	21,06	22,49	24,21	26	27,85	29,77
Span flat (m)	10,42	10,76	11,17	11,57	11,98	12,38
AR flat	5,15	5,15	5,15	5,15	5,15	5,15
Chord min. (m)	0,55	0,57	0,59	0,61	0,63	0,66
Chord max. (m)	2,5	2,89	2,69	2,78	2,88	2,98
Middle line length without riser (m)	5,59	5,79	6,03	6,27	6,51	6,75
Line consumption (m)	231	239	249	258	268	277
Weight(kg)*/**	2,85	3,05	3,25	3,35	3,55	3,75
Recom. weight range	60-75	70-85	80-95	90-105	100-115	110-130
Certified weight range (kg)	55-80	65-90	75-100	85-110	95-120	105-135
Classification EN/LTF	B	B	B	B	B	B

* Weight with light riser/ normal riser +150gr

** Light riser separatly sold

MATERIAL

Material top sail : DOMINICO 10D (27gr)
 Material bottom sail: DOMINICO 10D (27gr)
 Material Internal: Porcher Skytex 27 hard (27gr)
 Rigidfoil: 1,5mm Perlon transparent

Riser: Liros 13mm Kevlar, Cousin 7mm with Softlinks optional

KEY FEATURES

- 6 sizes with extended weight range
- 3 color combinations
- ZOOM handling
- 2 times 3d Shaping
- LE miniribs with internal sewing
- TE Miniribs with internal sewing
- Dirthole with Dirtchannel für eine selbstständige Schmutzentleerung
- new light compression innerbag
- riser with color differentiation (left/right)
- riser with BC-handle



